

EUROLUB CLEANPOWER C1 5W-30

Description / Applications:

A universal, fuel economy, specially composed motor oil, recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans. Due to its special composition this product can be applied in vehicles with modern three way catalysts and diesel particle filters. Due to its low SAPS content this motor oil contributes to the extension of the lifetime of particle filters for diesel engines.

Warning: *These oils have the lowest SAPS limits and may be unsuitable for use in some engines.*

Can be used with:

ACEA C1
Ford WSS-M2C934-B
Jaguar Land Rover STJLR.03.5005
JASO DL-1
Mazda

Delivery:

Art.-Nr. 213020	20 Liter	can
Art.-Nr. 213060	60 Liter	hobbock
Art.-Nr. 213208	208 Liter	drum
Art.-Nr. 213100	Container	IBC

Technical Data:

Data	Unit	Method	EUROLUB CLEANPOWER C1 5W-30
Density at 15°C	kg/L	D 4052	0,845
Viscosity at 40°C	cSt	D 445	58,4
Viscosity at 100°C	cSt	D 445	10,1
Viscosityindex (VI)		D 2270	161
Flash point (COC)	°C	D 92	238
Pourpoint	°C	D 6892	-35

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.