

EUROLUB ECO DXS 0W-20

Description/Applications:	ECO DXS 0W-20 is a synthetic low-friction engine oil. It is ideally suited for energy-saving, year-round use in modern passenger car engines. - Very stable viscosity behavior - Fuel economy - Suitable for catalytic converters - Very good cold starting properties
----------------------------------	--

Can be used with:	API SP (RC) / SN Plus ILSAC GF-5/GF-6a Chrysler MS-6395 GM dexos1tm Gen. 3 Ford WSS-M2C947-B1 Ford WSS-M2C962-A Fiat 9.55535-GSX/-CR1 GM 6094M
--------------------------	--

Delivery:	Art.-Nr. 255001	12 x 1 Liter	bottle
	Art.-Nr. 255005	4 x 5 Liter	can
	Art.-Nr. 255020	20 Liter	can
	Art.-Nr. 255060	60 Liter	hobbock
	Art.-Nr. 255208	208 Liter	drum
	Art.-Nr. 255100	Container	IBC

Technical Data:

Data	Unit	Method	EUROLUB ECO DXS 0W-20
Density at 15°C	kg/L	D 4052	0,840
Viscosity at 40°C	cSt	D 445	50,5
Viscosity at 100°C	cSt	D 445	8,9
Viscosityindex (VI)		D 2270	158
Flash point (COC)	°C	D 92	248
Pourpoint	°C	D 6892	-63

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.