

EUROLUB FORMEL 1 5W-40

Description / Applications:

FORMEL 1 5W-40 is a high-performance engine oil produced using HC synthetic oils with a wide area of application. Its high level of performance is achieved through the interaction of selected base oils and advanced additives.

Can be used with:

ACEA C3
API SN / CF
MB 229.31 / MB 229.51
VW 505.00 / 505.01
BMW Longlife-04
GM dexos2™
Ford WSS-M2C-917-A
Renault RN0700 / RN 0710
Porsche A40

Delivery:

Art.-Nr. 216005	4 x 5 Liter	can
Art.-Nr. 216060	60 Liter	hobbock
Art.-Nr. 216208	208 Liter	drum

Technical Data:

Data	Unit	Method	EUROLUB FORMEL 1 5W-40
Density at 15°C	kg/L	ASTM D 7042	0,848
Viscosity at 40°C	cSt	ASTM D 7042	93,89
Viscosity at 100°C	cSt	ASTM D 7042	15,2
Viscosityindex (VI)		ASTM D 7042	171
Flash point (COC)	°C	DIN EN ISO 2592	230
Pourpoint	°C	DIN EN ISO 3016	-33

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.