

EUROLUB GEAR TRANS M 75W-90

Description/Applications:

Lightrun gear oil for longer intervals.
The full performance is only achieved unmixed.
Optimal gear lubrication over a wide temperature range, even at very high or low outside temperatures.
Good protection of bearings and gears in heavy use at high loads.

Can be used with:

API GL-4
MB 235.11
MAN 341 Typ Z2/E1
VW 501 50
ZF TE-ML 16A/17A/19A/19C

Delivery:

Art.-Nr. 348020	20 Liter	plastic canister
Art.-Nr. 348060	60 Liter	hobbock
Art.-Nr. 348208	208 Liter	drum

Technical Data:

Data	Unit	Method	EUROLUB GEAR TRANS M 75W-90
Density at 15°C	kg/L	DIN 51 757	0,877
Viscosity at 40°C	mm ² /s	DIN 51 562-1	116,7
Viscosity at 100°C	mm ² /s	DIN 51 562-1	18,3
Viscosity Index (VI)		DIN ISO 2909	175
Flash point (COC)	°C	DIN ISO 2592	182
Pourpoint	°C	DIN ISO 3016	-42

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.