

## EUROLUB HD 5CX EXTRA 15W-40

### Description

HD 5CX EXTRA 15W-40 is an all-season multigrade engine oil. Exhaust gas turbocharging and charge air cooling place considerably higher mechanical and thermal demands on engine oils. HD 5CX EXTRA 15W-40 can safely cope with these tougher operating conditions, even with extended oil residence times. HD 5CX EXTRA 15W-40 is used in extremely highly stressed commercial vehicle diesel engines. HD 5CX EXTRA 15W-40 is recommended as a multigrade oil in viscosity grade SAE 15W-40 due to its extended service life and frequent use across seasons.

### Can be used with

ACEA E11  
API CK-4/SN  
JASO DH-2  
CAT ECF-3  
Cummins CES 20086  
Detroit Diesel 93K222  
Deutz III-18 LA  
Ford WSS-M2C171-F1  
Mack EOS-4.5  
MAN M 3775  
DTFR 15C100  
MTU Type 2.1  
Renault VI RLD-3  
Volvo VDS-4.5

### Delivery

|                 |           |      |
|-----------------|-----------|------|
| Art.-No. 228020 | 20 Liter  | can  |
| Art.-No. 228060 | 60 Liter  | drum |
| Art.-No. 228208 | 208 Liter | drum |
| Art.-No. 228100 | Container | IBC  |

### Technical Data

| Data                | Unit               | Method       | Value |
|---------------------|--------------------|--------------|-------|
| Density at 15°C     | kg/L               | DIN 51 757   | 0.874 |
| Viscosity at 40°C   | mm <sup>2</sup> /s | DIN 51 562   | 108.7 |
| Viscosity at 100°C  | mm <sup>2</sup> /s | DIN 51 562   | 14.3  |
| Viscosityindex (VI) | -                  | DIN ISO 2909 | 137   |
| Flash point (COC)   | °C                 | DIN ISO 2592 | 210   |
| Pourpoint           | °C                 | DIN ISO 3016 | -30   |