

EUROLUB SUPER PS-C 0W-20

Description/Applications:	SUPER PS-C 0W-20 is a modern low-friction multigrade engine oil based on synthesis technology. Carefully selected, highly effective additives give this high-performance engine oil the following outstanding properties: • Excellent shear stability • Very good cold start properties • A reliable lubricating film at very high operating conditions • Very good protection against wear, corrosion and foaming • Very good detergent and dispersant properties
----------------------------------	---

Can be used with:	ACEA C5 API SN Plus PSA B71 2010 Opel OV0401547-A20 Fiat 9.55535-DM1
--------------------------	---

Delivery:	Art.-Nr. 252001	12 x 1 Liter	bottle
	Art.-Nr. 252005	4 x 5 Liter	can
	Art.-Nr. 252020	20 Liter	can
	Art.-Nr. 252060	60 Liter	hobbock
	Art.-Nr. 252208	208 Liter	drum
	Art.-Nr. 252100	Container	IBC

Technical Data:

Data	Unit	Method	EUROLUB SUPER PS-C 0W-20
Density at 15°C	kg/L	D 4052	0,845
Viscosity at 40°C	cSt	D 445	43,90
Viscosity at 100°C	cSt	D 445	8,20
Viscosityindex (VI)		D 2270	165
Flash point (COC)	°C	D 92	230
Pourpoint	°C	D 6892	-41

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching / Germany Tel. +49 8165 9591 – 0, Fax +49 81659591 - 20 www.eurolub.com, info@eurolub.com	print: 28.11.2023, made 10.05.2021
	Referenz: D4009, 10.05.2020
	Name: 252xxx TDS EN
	Seite 1 von 1