

EUROLUB TOP 3000 Langzeitfett

Application: Properties:	TOP 3000 long-term grease is a yellow/green-fluorescent, semi-synthetic high-performance EP grease with very good adhesion. It is water resistant and very difficult to wash out.
-------------------------------------	---

Designation DIN 51502:	KP 2 G-30
-------------------------------	-----------

Application recommendations:	Top 3000 long-life grease is suitable for long-term lubrication of heavy construction machinery and agricultural equipment. • resistant to oxidation • work stable • extremely water resistant • particularly pronounced anti-corrosion properties • protects against fretting corrosion • high pressure absorption capacity
-------------------------------------	--

Delivery:	Art.-Nr. 707500 30 x 500 g cartridges
	Art.-Nr. 707015 15 kg plastik hobbock

Technical Data:			
Data:	Unit:	Method:	EUROLUB TOP 3000
Operating temperature for long-term lubrication	°C		-30 to +110
Short time admissible temperature peak value	°C		>150
Worked penetration	1/10 mm	ASTM D 217	265 to 295
Resistance to water		DIN ISO 51807-01	0-90
SKF Emcor Test		DIN ISO 51802	0/0
Thickener			spec. Calcium

The data provided are subject to change. Operating rules of the manufacturer. Characteristics are typical of current production data are subject to change. This should describe the products and should not therefore intended to assure certain properties. Obligation can not be derived.

EUROLUB GmbH Freisinger Strasse 25-27 85386 Eching bei München Tel. +49 8165 9591 - 0, Fax +49 81659591 - 20 www.eurolub.com , info@eurolub.com	print: 17.11.2020, made 17.10.2017
	Referenz: sieb4978, 01.01.2017
	Name: 707xxx_TDS_EN
	Seite 1 von 1