

Gazpromneft Premium N 20W-50



Engine oil



Semi-synthetic oil



Multigrade,
SAE 20W-50



For gasoline and
diesel engines



High engine
cleanliness



Special polymer
molecules

Gazpromneft Premium N 20W-50 - semi-synthetic engine oil designed for gasoline and diesel engines of passenger cars, SUVs and light commercial vehicles operated in hot climate regions. The use of synthetic base components improves stability to deposit formation, and enhanced neutralizing properties increase stability to fuel of variable quality.

Advantages

- Stable viscosity properties for reliable engine protection at elevated temperatures
- The retention of a strong oil film on engine parts, due to special polymer molecules, provides excellent protection against engine wear
- Ensures reliable engine protection when using fuels of variable quality due to a high Base Number reserve
- Reduces deposit formation on engine components through the use of synthetic base oils

Application



- Passenger cars, SUVs, vans, and light trucks from European and other manufacturers operating in hot climate regions
- Designed for gasoline and diesel engines (turbocharged and naturally aspirated) in a wide range of vehicles requiring SAE 20W-50 viscosity and meeting API SN or earlier performance levels

Specification	Gazpromneft Premium N 20W-50
API SN	✓

Standard physico-chemical characteristics

Indicators	Method	Gazpromneft Premium N 20W-50
Kinematic viscosity, mm ² /s: at 100 °C at 40 °C	ASTM D 445	166,7 18,4
Viscosity index	GOST 25371	124
Flash point, COC, °C	GOST 4333	235
Pour point, °C	GOST 20287	-32
Base number, mg KOH/g	ASTM D 2896	11,6
Density at 20 °C, kg/m ³	ASTM D 4052	884,5

The company's management system is certified in accordance with the international standards

ISO 9001



ISO 14001



ISO 45001

