



GERMAN TECHNOLOGY-GERMAN INNOVATION

WÜNSCHER Fahrzeugteile GmbH

Behrensallee 6 Pinneberg Germany

QUALITY CERTIFICATE

Wünscher Super HD Prime 20W-50

Properties

Super HD Prime 20W-50 is a mineral oil-based high-performance universal motor oil of viscosity class SAE 20W- 50.

Base oils of the most modern refinery technology and an innovative additive system tailored to this technology ensure compliance with today's practical requirements. Its outstanding properties include excellent lubrication reliability at high temperatures and extreme wear protection under all operating conditions. Cleaning additives prevent deposits, pistons and valves remain clean as well as the formation of black sludge. Engine cleanliness and low friction reduce energy losses and lower maintenance costs.

Application notes

Super HD Prime 20W-50 is a high-performance motor oil, universally applicable, even at high loads. Its performance spectrum covers the requirements of passenger car, petrol and diesel engines with and without turbocharging.

Service description

Specifications:

- API SL/CF
- ACEA A3/B4

Recommendations*:

- MB 229.1
- VW 502 00 / 505 00

TYPICAL PARAMETERS	METHODS	UNITS	SuperHD Prime 20W50
Density at 15°C	DIN 51 757	kg/m ³	885
Viscosity at 40°C	DIN 51 562	mm ² /s	157
Viscosity at 100°C	DIN 51 562	mm ² /s	18.4
Viscosity at -15°C	DIN 51 377	mPa.s	5960
Viscosity Index (VI)	DIN ISO 2909	-	132
Pour point	DIN ISO 3016	°C	-36
Flash point COC	DIN ISO 2592	°C	236
TBN	DIN ISO 3771	mg KOH/g	8.7

* meets the requirements of the OEM manufacturer
 The above values may vary within commercially accepted tolerances