



GERMAN TECHNOLOGY – GERMAN INNOVATION

WÜNSCHER Fahrzeugteile GmbH

Behrensallee 6 Pinneberg Germany

QUALITY CERTIFICATE

Wünscher Eurosynt Longlife 5W-30

Properties

Eurosynt Longlife 5W-30 is a HC-synthetic high- performance low viscosity engine oil with low sulphur, ash and phosphorus content (low SAP).

Base oils of the latest HC- synthesis techno- logy and a corresponding high-performance additive with lowered sulphate ash guarantee best wear protection and highest engine cleanliness. Excellent cold start behaviour ensures optimum lubrication reliabi- lity in the cold running phase. Extreme loads and high temperatu- res are safely mastered.

Eurosynt Longlife 5W-30 can be used under all operating conditions and contributes to environmental protection by reducing pollutant emissions.

Application notes

Eurosynt Longlife 5W-30 for modern car engines of the latest technology, especially with diesel particulate filter and exhaust gas aftertreatment of the manufacturers BMW, Mercedes- Benz, VW and Audi.

Eurosynt Longlife 5W-30 optimises the service life of exhaust gas purification systems and maintains their functionality.

Service description

Specifications:

- ACEAC3

Recommendations*:

- Porsche C30

Approval:

- VW 504 00 / 507 00
- MB 229.51
- BMW Longlife-04

TYPICAL PARAMETERS	METHODS	UNITS	Eurosynt Longlife 5W30
Density at 15°C	DIN 51 757	kg/m ³	851
Viscosity at 40°C	DIN 51 562	mm ² /s	68.5
Viscosity at 100°C	DIN 51 562	mm ² /s	11.8
Viscosity at -30°C	DIN 51 377	mPa.s	6450
Viscosity Index (VI)	DIN ISO 2909	-	168
Pour point	DIN ISO 3016	°C	-45
Flash point COC	DIN ISO 2592	°C	230
TBN	DIN ISO 3771	mg KOH/g	8.2

* meets the requirements of the OEM manufacturer

The above values may vary within commercially accepted tolerances

September 2024

Note:

No heavy metal was found in concentrations greater than 500 ppm. For this purpose, "metal" – molybdenum, manganese, calcium, zinc or magnesium.